



## The Sullair 375H Portable Air Compressor


375 cfm at 150 psig ■ 10.6 m<sup>3</sup>/min at 10 bar

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- E-Z lube axle
- Large tool box compartment
- Curbside instrument panel
- SSAM—Shutdown System and Annunciation Module
- Battery disconnect switch
- Idle warm-up valve
- Emergency stop
- Rocker type start switch
- Protective shutdown switches
- Fuel/Water separator
- Three-Stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Durable powder coat finish
- Wide track
- Galvanneal sheet metal
- Recessed tail lights
- Rear bumper

  
**SULLAIR**<sup>®</sup>  
*Always air. Always there.™*



**Total Accessibility**  
Routine maintenance is simplified.



**Large Tool Box Compartment**  
Sullair pneumatic tool sold separately.



**Rotary Screw Compressor by Sullair**  
The pioneer in rotary screw technology.



**Sullair AWF Compressor Fluid**  
Improved hot and cold weather lubrication. Longer compressor fluid life. Extended air end warranty.

**Designed for Total Accessibility and Reliability**

**Rotary Screw Compressor**

**Ample Service Doors**

- Large service doors provide access to fuel tank, engine, compressor air filters and tool compartment
- Rear service panel provides access to side-by-side compressor fluid cooler, engine air cooler and engine radiator
- Serviceable components within easy reach
- Routine maintenance is simplified
- Reduced downtime and service cost
- Service doors feature non-rusting hinges and stainless steel T-type door retainers

**Multi-Piece Canopy**

- Modular design reduces replacement costs
- Easily removed as one assembly for major service
- Exposed, single point lifting bail

**0 to 100% Capacity Control**

- Pneumatic inlet valve and unloaded starting

**Highway Towable Running Gear**

- 3" x 5" drawbar
- Adjustable height hitch (15", 17", 19")
- Quick-change hitch
- Screw jack with pad
- Transport security chains
- E-Z lube axle lubrication
- Heavy duty leaf spring suspension

**Curbside Instrument Panel**

- Hinged, padlockable cover
- Mechanical air pressure gauge, Powerview (John Deere) and Hourmeter (Caterpillar)
- Rocker type engine start switch
- Idle warm-up valve
- High/low pressure selector valve allows dual pressure capability without making mechanical adjustments

**SSAM—Shutdown System & Annunciation Module**

- Shutdown with annunciator light for high compressor temperature, high engine coolant temperature, low engine oil pressure and engine underspeed
- Low fuel shutdown

**Three-Stage Dry Type Air Filters**

- Separate filters for engine and compressor

**Durable, Baked-On Powder Coat Finish**

**Tier 3 Emission Compliant Engines**

**Air End Warranty**

- 2-year standard warranty
- 5-year or 10,000-hour warranty when continuously serviced at the recommended intervals with Sullair AWF Compressor Fluid and filters

**Quiet Operation**

- Meets US EPA sound requirements of 76 dBA @ 7 meters

**Customize the compressor to meet your specific requirements with Sullair's options**

Filtration for instrument quality air  
Aftercooler  
Special paint  
Hose reels, single and dual  
Spark arrestor  
Cold weather starting aid

Fuel level gauge  
Brakes (recommended where required by law)  
Mechanical parking brakes  
Ball hitch  
Air filter maintenance indicators

Gauge package (Caterpillar)  
Tachometer (Caterpillar)  
Block heater  
Ether starting aid (John Deere)

**SPECIFICATIONS, WEIGHTS AND DIMENSIONS—SULLAIR 375H PORTABLE COMPRESSOR**

Delivery @ Rated Pressure	Rated Pressure psig bar	Pressure Range psig bar	Designated Model	Weight* (wet) lbs kg	Weight* (dry) lbs kg	Length (drawbar) in mm	Length (canopy) in mm	Width in mm	Height in mm	Track Width in mm	Tire Size (load range)
375 acfm 177 l/s 10.6 m³/min	150 10	80–150 5.5–10	2-Wheel	4440 2014	4050 1787	156.1 3966	98.8 2510	77.2 1960	74 1880	67.5 1715	225/75D15
			Less Running Gear	4195 1903	3805 1726	– –	98.8 2510	59.3 1506	63.6 1616	– –	–

Engine Make	Engine Type	Engine Model	Displacement in³ cc	Cylinders	Bore and Stroke in mm	Rated Speed rpm	Rated Power hp kW
John Deere (Tier 3 emissions compliant)	Diesel	4045HF285	275 4507	4	4.19 x 5.00 106 x 127	2200	140 104
Caterpillar (Tier 2)	Diesel	3054C	269 4400	4	4.13 x 5.00 106 x 127	2200	129 96
Caterpillar (Tier 3 emissions compliant)	Diesel	C4.4	269 4400	4	4.13 x 5.00 105 x 127	2200	130 97

Capacity per CAGI/PNEUROP PN2CPTC3. (Annex D to ISO 1217)

CAT T2 engine available outside North America and the EU Countries. \* Weights are for JD Diesel. For CAT, deduct 20 lbs



**Sullair**  
3700 East Michigan Boulevard  
Michigan City, IN 46360  
Telephone: 219-879-5451  
www.sullair.com

© Copyright 2014 Sullair. All rights reserved.  
The color green is a registered trademark of Sullair.  
Specifications subject to change without notice.  
SSL-1082EN 1404R

