



Sullair Performance Lubricant
SULLAIR SRF 1/4000®
Standard Replacement Fluid
for Stationary Vacuum Compressors



A premium-performance fluid, SRF 1/4000 combines the long life of synthetics with the economy of petroleum-based fluids. SRF 1/4000 is a lubricant, coolant and sealant.

- Long life at a good value
- Low volatility
- Enhanced lubrication
- High viscosity
- Year-round performance

Your 1-year/4000-hour advantage

SRF 1/4000 is a highly refined, semi-synthetic paraffinic oil produced by a patented hydrotreating process. Using SRF 1/4000 in a machine for one year or 4000 hours reduces labor and downtime costs for fluid changeout. It is an excellent choice for machines not running continuously but still require a high viscosity index.

FEATURES AND BENEFITS

4000-hour life

The hydro-treated petroleum base resists breakdown and varnish and has a high viscosity index for stability against shear and high temperatures. It also exhibits excellent demulsibility and resists foaming.

Reduces maintenance

The long life of SRF 1/4000 helps reduce downtime and labor for changeout when compared to standard mineral-based fluids. Being less volatile, it requires less fluid for top-off.

Lubricates effectively

SRF 1/4000 has excellent anti-wear properties and corrosion protection. Its enhanced lubrication provides an excellent environment for rolling element bearings.

Good value

SRF 1/4000 provides performance at the right price.

Performs in all weather

One fluid with year-round reliable performance in both low and high temperatures.

Comprehensive support

We stand ready with fluid professionals who can help you with any fluid-related issues or questions. Our exclusive Compressor Fluid Analysis program thoroughly evaluates your compressor fluid and provides critical data including: lubricant performance history, drain intervals, and environmental conditions that may affect your fluid. Choosing the right fluid and testing it regularly can help you build an optimized preventive maintenance program designed to help minimize downtime.

PRODUCT INFORMATION



| PACKAGING | |
|-----------|-------------|
| Size | Part Number |
| 5 Gallon | 250019-662 |
| 55 Gallon | 250019-663 |

| TYPICAL PROPERTIES | | |
|--------------------|---------------|------|
| Viscosity | 104°F (40°C) | 36.0 |
| | 212°F (100°C) | 6.0 |
| Flash Point | 388°F (198°C) | |
| Hours | 4000 | |



FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.