





# Sullair Performance Lubricant SULLAIR SRF II/8000®

## Standard Replacement Fluid for Stationary Compressors

SRF II/8000 is a highly refined standard replacement fluid for stationary air compressors. This long-life, hydrotreated, petroleum-based fluid helps reduce maintenance, operation and disposal costs.



- Lasts long up to 8000 hours or one year
- Resists breakdown from shearing and high temperatures

#### High-quality — value-priced

With excellent viscosity, SRF II/8000 is a high-quality fluid offering high resistance to breakdown for stable operation at a wide range of temperatures. This hydro-treated fluid is highly demulsifiable, increasing the efficiency of oil/condensate separators. And SRF II/8000 is a good value — providing a budget-friendly long life.

#### FEATURES AND BENEFITS

#### **Long-lasting**

Hydro-treated petroleum base resists breakdown and varnish.

#### **Lubricates effectively**

Excellent anti-wear properties are designed to provide long-lasting lubrication.

#### **Lowers expenses**

Long changeout intervals cut maintenance labor and fluid disposal costs. Non-hazardous classification of used fluid reduces disposal costs further.

#### **Comprehensive support**

We stand ready with fluid professionals who can help with any fluid-related issues or questions. Our exclusive compressor fluid analysis program thoroughly evaluates your compressor fluid and provides critical data including: lubricant performance history, drain intervals and environmental conditions that may affect your fluid. Choosing the right fluid and testing it regularly can help you build an optimized preventive maintenance program designed to help minimize downtime.

### **PRODUCT INFORMATION**



PACKAGING		
Size	Part Number	
5 Gallon	02250118-160	
55 Gallon	02250118-162	

TYPICAL PROPERTIES		
Viscosity	104°F (40°C)	35.6
	212°F (100°C)	5.7
Flash Point	431°F (222°C)	
Hours	8000	



FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.



